Freshness Meets Innovation

CONTACT US
www.hemcogroup.com
hello@hemcogroup.com
+91 9198801112, +91 8114177999

*Pro*Chill™

HEMCO

Under Counter Refrigerators

Under Counter Refrigerator (RDE-001)

Specification:
- 60 mm thick polyurethane insulation for better energy effciency.
- Stainless steel AISI 304 internal & external panels.
- Refrigerated models have operating temperature that can be adjusted -2 to 10 °C.
- Self Closing Doors with magnetic Gasket.
- Forced air circulation for rapid cooling & an even temperature distribution.
- 4 Nos. adjustable S.S. wire mesh shelves.

Pick Up Counter with UCR (RDE-002)

Specification:
- 60 mm thick polyurethane insulation for better energy effciency.
- Stainless steel AISI 304 internal & external panels.
- Refrigerated models have operating temperature that can be adjusted -2 to 10 °C.
- Self Closing Doors with magnetic Gasket.
- Forced air circulation for rapid cooling & an even temperature distribution.
- 4 Nos. adjustable S.S. wire mesh shelves.
- Two number of overhead shelves are provided for easy pick up

Mac-Line cum UCR (RDE-002)

Specification:
- 60 mm thick polyurethane insulation for better energy effciency.
- Stainless steel AISI 304 internal & external panels.
- Refrigerated models have operating temperature that can be adjusted -2 to 10 °C.
- Self Closing Doors with magnetic Gasket.
- Forced air circulation for rapid cooling & an even temperature distribution.
- 4 Nos. adjustable S.S. wire mesh shelves.
- 8 Nos. (1/6)*100 Deep cold GN Pan with lid for store mizzas.

Vertical Refrigerators

Specification:
- 60 mm thick polyurethane insulation for better energy effciency.
- Stainless steel AISI 304 internal & external panels including back panel.
- Large storage area suitable to contain 2/1 GN pan & 6 Nos. adjustable
- S.S. wire mesh shelves.
- Refrigerated models have operating temperature that can be adjusted -2 to 10 °C.
- Self Closing Doors with magnetic Gasket.
- Auto defrosting and auto evaporation of condensation water.
- Digital controller allows for temperature & parameter setting.
- Performance at ambient temperature of + 43 °C.
- Forced air circulation for rapid cooling & an even temperature distribution.

Model:

Single Doorl Double Door

Glass Door Refrigerator

Specification:
- 60 mm thick polyurethane insulation for better energy effciency.
- Stainless steel AISI 304 internal & external panels including back panel.
- Large storage area suitable to contain 2/1 GN pan & 6 Nos. adjustable
- S.S. wire mesh shelves.
- Refrigerated models have operating temperature that can be adjusted -2 to 10 °C.
- Self Closing Doors with magnetic Gasket.
- Auto defrosting and auto evaporation of condensation water.
- Digital controller allows for temperature & parameter setting.
- Performance at ambient temperature of + 43 °C.
- Forced air circulation for rapid cooling & an even temperature distribution..

Model:

Single Doorl Double Door

Modular Cold room

Specification:
- Designed for applications having ambient conditions of 38°C to 46°C.
- Air cooled condenser refrigeration system with Hermatic / Semi Hermatic Compressor 407C / 404A refrigerant.
- Built in pressure safety switches & reputed make components and control valves.
- Enhanced grill design gives increase in free-air area.
- Units are designed for quiet and energy efficient operations.
- Fully loaded electrical control panel with micro processor based temperature controller.